# Latch Intercom Installation Requirements.

#### Screen

• Brightness: 1000 nits

• Viewing angle: 176 degrees

• Size: 7 inch diagonal

Automatic brightness adjustment

### Protection

- Anti-reflective coating
- Anti-fingerprint coating
- Made with Corning® Gorilla®
   Glass 3

#### Dimensons

- 12.82 x 6.53 x 1.38 in inches
- 325.6 x 166.0 x 35.1 in mm

## Camera

 External camera requiring separate networking and power

#### Power

Power consumption

-Typical: 20W -Max: 50W

• 2-wire: 12 - 24VDC

• Power over Ethernet: 802.3bt with 50W+

#### Network

• Ethernet: 10/100/1000mbps

WiFi: 2.4GHz / 5GHz 802.11 a/b/g/n/ac

Cellular Cat 1

• Bluetooth 4.2

DHCP or Static IP

## **Durability**

- Materials: stainless steel, glass fiber
   reinforced resin, and impact-resistant glass
- IP65 dust and water resistance
- Tamper detection
- Operating -30C to 60C

# Compliance


- FCC / IC
- PTCRB
- UL62368-1
- UL294


#### Audio

- 90dB output (0.5m, 1kHz)
- Dual mic
- Echo cancellation and noise reduction
- Automatic volume adjustment


## Accessibility

- ADA compliant
- Supports audio instructions and navigation
- Tactile buttons
- Supports TTY/RTT






4 Intercom Rear View with Mounting Plate





2 Intercom Side View




**ADA Compliance Requirement** 

5 Intercom Front View





3 Intercom Rear View



6 Mounting Plate Front View

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
LATCHABLE, INC. ANY REPRODUCTION IN
PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF LATCHABLE, INC. IS
PROHIBITED.

INTERCOM INSTALLATION DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

LATCH

450 W 33RD ST
FLOOR 12
NEW YORK, NY 10001
USA

REV
D

770-00012

DO NOT SCALE DRAWING

SHEET 1 OF 1